

深圳市晶彩世界科技有限公司

产品规格书

Product Type: 6.5" TFT LCD Module

LCD Interface: 50PIN TTL

Luminance: 500 cd/m²

Module No: JCQ065TN-24A

CUSTOMER APPROVED	PREPARE BY	CHECK BY	APPROVED BY
SUPPLIER APPROVED	PREPARE BY	CHECK BY	APPROVED BY

--	--	--

Contents

1. General Specifications	1
2. Pin Assignment	2
2.1. TFT LCD Panel Driving Section	2
3. Operation Specifications	5
3.1. Absolute Maximum Ratings	5
3.1.1. Typical Operation Conditions	5
3.1.2. Current Consumption	6
3.1.3. Backlight Driving Conditions	6
3.2. Power Sequence	7
3.3. Timing Characteristics	8
3.3.1. Timing Conditions	8
3.3.2. Data Input Format	9
3.3.3. Timing	10
4. Optical Specifications	11
5. Reliability Test Items	15
6. General Precautions	16
6.3. Safety	16
6.4. Handling	16
6.5. Static Electricity	16
6.6. Storage	16
6.7. Cleaning	16
7. Mechanical Drawing	17
8. Package Drawing	18
8.1. Packaging Material Table	18
8.2. Packaging Quantity	18
8.3. Packaging Drawing	19

1. General Specifications

No.	Item	Specification	Remark
1	LCD size	6.5 inch(Diagonal)	
2	Driver element	a-Si TFT active matrix	
3	Resolution	800 × 3(RGB) × 480	
4	Display mode	Normally white, Transmissive	
5	Dot pitch	0.05975(W) × 0.1598 (H) mm	
6	Active area	143.400 (W) × 76.704 (H) mm	
7	Module size	155.2(W) × 89.4(H) × 5.5(D) mm	Note1
8	Surface treatment	Anti-Glare	
9	Color arrangement	RGB-stripe	
10	Interface	Digital	
11	View direction(Gray Inversion)	6 O'Clock	
12	Backlight power consumption	1.488 W(Typ.)	
13	Panel power consumption	0.235W(Typ.)	
14	Weight	0.1269kg	

Note1: Refer to Mechanical Drawing.

2. Pin Assignment

2.1. TFT LCD Panel Driving Section

FPC Connector is used for the module electronics interface. The recommended model is FH12A-50S-0.5SH manufactured by Hirose.

Pin No.	Symbol	I/O	Function	Remark
1	V _{LED+}	P	Power for LED backlight (Anode)	
2	V _{LED+}	P	Power for LED backlight (Anode)	
3	V _{LED-}	P	Power for LED backlight (Cathode)	
4	V _{LED-}	P	Power for LED backlight (Cathode)	
5	GND	P	Power ground	
6	V _{COM}	I	Common voltage	
7	DV _{DD}	P	Power for Digital Circuit	
8	MODE	I	DE/SYNC mode select	Note 1
9	DE	I	Data Input Enable	
10	VS	I	Vertical Sync Input	
11	HS	I	Horizontal Sync Input	
12	B7	I	Blue data(MSB)	
13	B6	I	Blue data	
14	B5	I	Blue data	
15	B4	I	Blue data	
16	B3	I	Blue data	
17	B2	I	Blue data	
18	B1	I	Blue data	Note 2
19	B0	I	Blue data(LSB)	Note 2
20	G7	I	Green data(MSB)	
21	G6	I	Green data	
22	G5	I	Green data	
23	G4	I	Green data	
24	G3	I	Green data	

25	G2	I	Green data	
26	G1	I	Green data	Note 2
27	G0	I	Green data(LSB)	Note 2
28	R7	I	Red data(MSB)	
29	R6	I	Red data	
30	R5	I	Red data	
31	R4	I	Red data	
32	R3	I	Red data	
33	R2	I	Red data	
34	R1	I	Red data	Note 2
35	R0	I	Red data(LSB)	Note 2
36	GND	P	Power Ground	
37	DCLK	I	Sample clock	Note 3
38	GND	P	Power Ground	
39	L/R	I	Left / right selection	Note 4,5
40	U/D	I	Up/down selection	Note 4,5
41	V _{GH}	P	Gate ON Voltage	
42	V _{GL}	P	Gate OFF Voltage	
43	AV _{DD}	P	Power for Analog Circuit	
44	RESET	I	Global reset pin.	Note 6
45	NC	-	No connection	
46	V _{COM}	I	Common Voltage	
47	DITHB	I	Dithering function	Note 7
48	GND	P	Power Ground	
49	NC	-	No connection	
50	NC	-	No connection	

I: input, O: output, P: Power

Note 1: DE/SYNC mode select. Normally pull high.

When select DE mode, MODE="1", VS and HS must pull high.

When select SYNC mode, MODE="0", DE must be grounded.


Note 2: When input 18 bits RGB data, the two low bits of R,G and B data must be grounded.

Note 3: Data shall be latched at the falling edge of DCLK.

Note 4: Selection of scanning mode

Setting of scan control input		Scanning direction
U/D	L/R	
GND	DV _{DD}	Up to down, left to right
DV _{DD}	GND	Down to up, right to left
GND	GND	Up to down, right to left
DV _{DD}	DV _{DD}	Down to up, left to right

Note 5: Definition of scanning direction.
Refer to the figure as below:



:

Note 6: Global reset pin. Active low to enter reset state. Suggest to connect with an RC reset circuit for stability. Normally pull high.

Note 7: Dithering function enable control, normally pull high.
When DITHB="1", Disable internal dithering function,
When DITHB="0", Enable internal dithering function,

3. Operation Specifications

3.1. Absolute Maximum Ratings

Item	Symbol	Values		Unit	Remark
		Min.	Max.		
Power voltage	DV_{DD}	-0.3	5.0	V	
	AV_{DD}	6.5	13.5	V	
	V_{GH}	-0.3	40.0	V	
	V_{GL}	-20.0	0.3	V	
	$V_{GH}-V_{GL}$	-	40.0	V	
Operation Temperature	T_{OP}	-20	70	°C	
Storage Temperature	T_{ST}	-30	80	°C	
LED Reverse Voltage	V_R	-	1.2	V	Each LED Note 2
LED Forward Current	I_F	-	25	mA	Each LED

Note 1: The absolute maximum rating values of this product are not allowed to be exceeded at any times. Should a module be used with any of the absolute maximum ratings exceeded, the characteristics of the module may not be recovered, or in an extreme case, the module may be permanently destroyed.

Note 2: V_R Conditions: Zener Diode 20mA

3.1.1. Typical Operation Conditions

Item	Symbol	Values			Unit	Remark
		Min.	Typ.	Max.		
Power voltage	DV_{DD}	3.0	3.3	3.6	V	Note 2
	AV_{DD}	10.2	10.4	10.6	V	
	V_{GH}	15.3	16.0	16.7	V	
	V_{GL}	-7.7	-7.0	-6.3	V	
Input signal voltage	V_{COM}	3.6	3.8	4.0	V	
Input logic high voltage	V_{IH}	0.7 DV_{DD}	-	DV_{DD}	V	Note 3
Input logic low voltage	V_{IL}	0	-	0.3 DV_{DD}	V	

Note 1: Be sure to apply DV_{DD} and V_{GL} to the LCD first, and then apply V_{GH} .

Note 2: DV_{DD} setting should match the signals output voltage (refer to Note 3) of customer's system board.

Note 3: DCLK,HS,VS,RESET,U/D, L/R,DE,R0~R7,G0~G7,B0~B7,MOD

3.1.2. Current Consumption

Item	Symbol	Values			Unit	Remark
		Min.	Typ.	Max.		
Current for Driver	I_{GH}	-	0.6	1	mA	
	I_{GL}	-	0.6	1	mA	
	IDV_{DD}	-	4	10	mA	
	$I_{AV_{DD}}$	-	20	50	mA	

3.1.3.Backlight Driving Conditions


Item	Symbol	Values			Unit	Remark
		Min.	Typ.	Max.		
Voltage for LED backlight	V_L	9.0	9.3	9.6	V	Note 1
Current for LED backlight	I_L	-	160	-	mA	
LED life time	-	20,000	-	-	Hr	Note 2

Note 1: The LED Supply Voltage is defined by the number of LED at $T_a=25^{\circ}\text{C}$ and $I_L=160\text{mA}$.


Note 2: The "LED life time" is defined as the module brightness decrease to 50% original brightness at $T_a=25^{\circ}\text{C}$ and $I_L=160\text{mA}$. The LED lifetime could be decreased if operating I_L is larger than 160mA.

3.2. Power Sequence

1. Power on:



2. Power off:



Note: Data include DCLK,POL,OEV,CKV,STVU,STVD,STHL,STHR,LD,R0~R5,G0~G5,B0~B5

3.3. Timing Characteristics

3.3.1. Timing Conditions

Item	Symbol	Values			Unit	Remark
		Min.	Typ.	Max.		
HS setup time	T_{hst}	8	-	-	ns	
HS hold time	T_{hhd}	8	-	-	ns	
VS setup time	T_{vst}	8	-	-	ns	
VS hold time	T_{vhd}	8	-	-	ns	
Data setup time	T_{dsu}	8	-	-	ns	
Data hole time	T_{dhd}	8	-	-	ns	
DE setup time	T_{esu}	8	-	-	ns	
DE hole time	T_{ehd}	8	-	-	ns	
DV _{DD} Power On Slew rate	T_{POR}	-	-	20	ms	From 0 to 90% DV _{DD}
RESET pulse width	T_{Rst}	1	-	-	ms	
DCLK cycle time	T_{coh}	20	-	-	ns	
DCLK pulse duty	T_{cwh}	40	50	60	%	

3.3.2 Data Input Format




Figure 3. 1 Horizontal input timing diagram.




Figure 3. 2 Vertical input timing diagram.

3.3.3. Timing

Item	Symbol	Values			Unit	Remark
		Min.	Typ.	Max.		
Horizontal Display Area	thd	-	800	-	DCLK	
DCLK Frequency	fclk	26.4	33.3	46.8	MHz	
One Horizontal Line	th	862	1056	1200	DCLK	
HS pulse width	thpw	1	-	40	DCLK	
HS Blanking	thb	46	46	46	DCLK	
HS Front Porch	thfp	16	210	354	DCLK	

Item	Symbol	Values			Unit	Remark
		Min.	Typ.	Max.		
Vertical Display Area	tvd	-	480	-	TH	
VS period time	tv	510	525	650	TH	
VS pulse width	tvpw	1	-	20	TH	
VS Blanking	tvb	23	23	23	TH	
VS Front Porch	tvfp	7	22	147	TH	

4. Optical Specifications

Item	Symbol	Condition	Values			Unit	Remark
			Min.	Typ.	Max.		
Viewing angle (CR≥ 10)	θ_L	$\Phi=180^\circ$ (9 o'clock)	60	70	-	degree	Note 1
	θ_R	$\Phi=0^\circ$ (3 o'clock)	60	70	-		
	θ_T	$\Phi=90^\circ$ (12 o'clock)	40	50	-		
	θ_B	$\Phi=270^\circ$ (6 o'clock)	60	70	-		
Response time	T_{ON}	Normal $\theta=\Phi=0^\circ$	-	10	20	msec	Note 3
	T_{OFF}		-	15	30	msec	Note 3
Contrast ratio	CR		400	500	-	-	Note 4
Color chromaticity	W_X		0.28	0.31	0.34	-	Note 2 Note 5 Note 6
	W_Y		0.30	0.33	0.36	-	
Luminance	L		400	500	-	cd/m ²	Note 6
Luminance uniformity	Y_U		70	75	-	%	Note 7

Test Conditions:

1. $DV_{DD} = 3.3V$, $I_L = 160mA$ (Backlight current), the ambient temperature is $25^\circ C$.
2. The test systems refer to Note 2.

Note 1: Definition of viewing angle range




Fig. 4-1 Definition of viewing angle

Note 2: Definition of optical measurement system.

The optical characteristics should be measured in dark room. After 30 minutes operation, the optical properties are measured at the center point of the LCD screen. (Response time is measured by Photo detector TOPCON BM-7, other items are measured by BM-5A/Field of view: 1°/Height: 500mm.)




Fig. 4-2 Optical measurement system setup

Note 3: Definition of Response time

The response time is defined as the LCD optical switching time interval between "White" state and "Black" state. Rise time (T_{ON}) is the time between photo detector output intensity changed from 90% to 10%. And fall time (T_{OFF}) is the time between photo detector output intensity changed from 10% to 90%.




Fig. 4-3 Definition of response time

Note 4: Definition of contrast ratio

$$\text{Contrast ratio (CR)} = \frac{\text{Luminance measured when LCD on the "White" state}}{\text{Luminance measured when LCD on the "Black" state}}$$

Note 5: Definition of color chromaticity (CIE1931)

Color coordinates measured at center point of LCD.

Note 6: Definition of luminance: Measured at the center area of the panel when LCD panel is driven at "white" state

Note 7: Definition of Luminance Uniformity

Active area is divided into 9 measuring areas (Refer to Fig. 4-4).Every measuring point is placed at the center of each measuring area.

$$\text{Luminance Uniformity (Yu)} = \frac{B_{min}}{B_{max}}$$

L-----Active area length W----- Active area width




Fig. 4-4 Definition of measuring points

B_{max} : The measured maximum luminance of all measurement position.

B_{min} : The measured minimum luminance of all measurement position.

6. General Precautions

6.3. Safety

Liquid crystal is poisonous. Do not put it in your mouth. If liquid crystal touches your skin or clothes, wash it off immediately by using soap and water.

6.4. Handling

1. The LCD panel is plate glass. Do not subject the panel to mechanical shock or to excessive force on its surface.
2. The polarizer attached to the display is easily damaged. Please handle it carefully to avoid scratch or other damages.
3. To avoid contamination on the display surface, do not touch the module surface with bare hands.
4. Keep a space so that the LCD panels do not touch other components.
5. Put cover board such as acrylic board on the surface of LCD panel to protect panel from damages.
6. Transparent electrodes may be disconnected if you use the LCD panel under environmental conditions where the condensation of dew occurs.
7. Do not leave module in direct sunlight to avoid malfunction of the ICs.

6.5. Static Electricity

1. Be sure to ground module before turning on power or operating module.
2. Do not apply voltage which exceeds the absolute maximum rating value.



6.6. Storage

1. Store the module in a dark room where must keep at $25\pm 10^{\circ}\text{C}$ and 65%RH or less.
2. Do not store the module in surroundings containing organic solvent or corrosive gas.
3. Store the module in an anti-electrostatic container or bag.

6.7. Cleaning

1. Do not wipe the polarizer with dry cloth. It might cause scratch.
2. Only use a soft sloth with IPA to wipe the polarizer, other chemicals might permanent damage to the polarizer.

1	2	3	6	7	8
由 Autodesk 教育版产品制作			由 Autodesk 教育版产品制作		
Customer Name: 客户名称:		Customer's Code: 客户料号:		第三视角	
Approved by: 承认:		Module NO.: 模組料号:		A0	
Approval Date: 承认日期:		Edition: 版本号:		模组成品图	





RoHS

- Notes:
1. Unit:mm
 2. Do not scale drawing
 3. All radii without dimension R0.20mm
 4. Luminous intensity (9 AVG):
Module:650cd/m²(Min), 700cd/m²(Typ)
 5. Uniformity:80%(Min)
 6. The color coordinates:
VF:9.0V(Min); 9.9V(Typ); 10.5V(Max); IF:160mA(Typ)

	MIN	TYP	MAX
X	0.25	0.30	0.35
Y	0.26	0.31	0.36

7. Modification rev. number
8. draft angle 1.0°
9. General Tolerance:±0.20mm
10. Mark mold cavity identification in recess approximately where indicated
11. "*" For important dimension "()" for reference dimension
12. Rolls must be compiled. (Use Lead-Free process)



NO.	REVISE (修改者)	DESCRIPTION (修改内容)	Check by: (审查)	Approval By: (承认)	DATE (日期)	REV (修改)	Design by: (设计)
15		产品标签					
14		美纹胶					
13		PET拉把					
12		单面胶					
11		防刮标签					
10		美纹胶					
9		6.50W 玻璃					
8		DBEF					
7		增光膜					
6		扩散膜					
5		反射膜					
4		PCB+LED+PC					
3		下铁框					
2		导光板					
1		胶框					

NO.	REVISE (修改者)	DESCRIPTION (修改内容)	Check by: (审查)	Approval By: (承认)	DATE (日期)	REV (修改)	Design by: (设计)
15		产品标签					
14		美纹胶					
13		PET拉把					
12		单面胶					
11		防刮标签					
10		美纹胶					
9		6.50W 玻璃					
8		DBEF					
7		增光膜					
6		扩散膜					
5		反射膜					
4		PCB+LED+PC					
3		下铁框					
2		导光板					
1		胶框					

NO.	REVISE (修改者)	DESCRIPTION (修改内容)	Check by: (审查)	Approval By: (承认)	DATE (日期)	REV (修改)	Design by: (设计)
15		产品标签					
14		美纹胶					
13		PET拉把					
12		单面胶					
11		防刮标签					
10		美纹胶					
9		6.50W 玻璃					
8		DBEF					
7		增光膜					
6		扩散膜					
5		反射膜					
4		PCB+LED+PC					
3		下铁框					
2		导光板					
1		胶框					

NO.	REVISE (修改者)	DESCRIPTION (修改内容)	Check by: (审查)	Approval By: (承认)	DATE (日期)	REV (修改)	Design by: (设计)
15		产品标签					
14		美纹胶					
13		PET拉把					
12		单面胶					
11		防刮标签					
10		美纹胶					
9		6.50W 玻璃					
8		DBEF					
7		增光膜					
6		扩散膜					
5		反射膜					
4		PCB+LED+PC					
3		下铁框					
2		导光板					
1		胶框					

NO.	REVISE (修改者)	DESCRIPTION (修改内容)	Check by: (审查)	Approval By: (承认)	DATE (日期)	REV (修改)	Design by: (设计)
15		产品标签					
14		美纹胶					
13		PET拉把					
12		单面胶					
11		防刮标签					
10		美纹胶					
9		6.50W 玻璃					
8		DBEF					
7		增光膜					
6		扩散膜					
5		反射膜					
4		PCB+LED+PC					
3		下铁框					
2		导光板					
1		胶框					

NO.	REVISE (修改者)	DESCRIPTION (修改内容)	Check by: (审查)	Approval By: (承认)	DATE (日期)	REV (修改)	Design by: (设计)
15		产品标签					
14		美纹胶					
13		PET拉把					
12		单面胶					
11		防刮标签					
10		美纹胶					
9		6.50W 玻璃					
8		DBEF					
7		增光膜					
6		扩散膜					
5		反射膜					
4		PCB+LED+PC					
3		下铁框					
2		导光板					
1		胶框					

NO.	REVISE (修改者)	DESCRIPTION (修改内容)	Check by: (审查)	Approval By: (承认)	DATE (日期)	REV (修改)	Design by: (设计)
15		产品标签					
14		美纹胶					
13		PET拉把					
12		单面胶					
11		防刮标签					
10		美纹胶					
9		6.50W 玻璃					
8		DBEF					
7		增光膜					
6		扩散膜					
5		反射膜					
4		PCB+LED+PC					
3		下铁框					
2		导光板					
1		胶框					

NO.	REVISE (修改者)	DESCRIPTION (修改内容)	Check by: (审查)	Approval By: (承认)	DATE (日期)	REV (修改)	Design by: (设计)
15		产品标签					
14		美纹胶					
13		PET拉把					
12		单面胶					
11		防刮标签					
10		美纹胶					
9		6.50W 玻璃					
8		DBEF					
7		增光膜					
6		扩散膜					
5		反射膜					
4		PCB+LED+PC					
3		下铁框					
2		导光板					
1		胶框					

NO.	REVISE (修改者)	DESCRIPTION (修改内容)	Check by: (审查)	Approval By: (承认)	DATE (日期)	REV (修改)	Design by: (设计)
15		产品标签					
14		美纹胶					
13		PET拉把					
12		单面胶					
11		防刮标签					
10		美纹胶					
9		6.50W 玻璃					
8		DBEF					
7		增光膜					
6		扩散膜					
5		反射膜					
4		PCB+LED+PC					
3		下铁框					
2		导光板					
1		胶框					

NO.	REVISE (修改者)	DESCRIPTION (修改内容)	Check by: (审查)	Approval By: (承认)	DATE (日期)	REV (修改)	Design by: (设计)
15		产品标签					
14		美纹胶					
13		PET拉把					
12		单面胶					
11		防刮标签					
10		美纹胶					
9		6.50W 玻璃					
8		DBEF					
7		增光膜					
6		扩散膜					
5		反射膜					
4		PCB+LED+PC					
3		下铁框					
2		导光板					
1		胶框					

NO.	REVISE (修改者)	DESCRIPTION (修改内容)	Check by: (审查)	Approval By: (承认)	DATE (日期)	REV (修改)	Design by: (设计)
15		产品标签					
14		美纹胶					
13		PET拉把					
12		单面胶					
11		防刮标签					
10		美纹胶					
9		6.50W 玻璃					
8		DBEF					
7		增光膜					
6		扩散膜					
5		反射膜					
4		PCB+LED+PC					
3		下铁框					
2		导光板					
1		胶框					

NO.	REVISE (修改者)	DESCRIPTION (修改内容)	Check by: (审查)	Approval By: (承认)	DATE (日期)	REV (修改)	Design by: (设计)
15		产品标签					
14		美纹胶					
13		PET拉把					
12		单面胶					
11		防刮标签					
10		美纹胶					
9		6.50W 玻璃					
8		DBEF					
7		增光膜					
6		扩散膜					
5</							

8. Package Drawing

8.1. Packaging Material Table

No.	Item	Model (Material)	Dimensions(mm)	Unit Weight (kg)	Quantity	Remark
1	LCM Module	AT065TN14	155.2 × 89.4 × 5.5	0.1269	50pcs	
2	Partition	BC Corrugated paper	512 × 351 × 232	1.757	1set	
4	Corrugated Bar	B Corrugated paper	512 × 68 × 33	0.058	4pcs	
5	Dust-Proof Bag	PE	700 × 530	0.060	1pcs	
6	A/S Bag	PE	178 × 160	0.002	50pcs	
7	Carton	Corrugated paper	530 × 355 × 255	1.100	1 pcs	
8	Total weight	9.594kg ± 5%				

8.2. Packaging Quantity

Total LCM quantity in Carton: no. of Partition 2 Rows × quantity per Row 25 = 50
--

8.3. Packaging Drawing

